

EATON

Cutler-Hammer

Halyester™ Switch

Product Focus



Product Description

Eaton's new Halyester enclosed safety switch provides customers with a strong, yet lightweight heavy-duty, corrosion-resistant, NEMA® 4X switch that withstands salt environments and general outdoor conditions better than standard 304-grade stainless steel at a more competitive price point than other non-metallic enclosures.

Halyester is the trade name for Eaton's fiberglass-reinforced polyester enclosures that have been employed throughout Europe and Asia, in extremely harsh environmental conditions, for over 30 years.

Halyester has proven its reliability from the cold northern coasts of Scandinavia to the hot, tropical areas of the Middle and Far East, and Africa.

Halyester is used as the basic construction material because of its excellent mechanical and electrical properties and corrosion-free characteristics. This guarantees a maintenance-free and reliable operation for many years. After its useful lifetime, Halyester can be fully recycled. The polyester used is thermo setting, which means that mechanical and electrical properties are maintained also under higher temperatures.

By employing a polycarbonate door, the Halyester Safety Switch provides an industry-exclusive clear cover option. This feature provides safety from potential arc flashes by allowing users to visibly check both the contact position and blown fuse indication without opening the door.

Also, with the use of the clear cover option, all product labels are moved to the inside of the door, making the Halyester switch ideal for food processing areas where there are concerns of contaminants entering the food. There is nothing on the exterior of the switch that could possibly contaminate food batches.

The Halyester enclosure is wrapped around Eaton's industry-leading K-Switch mechanism. With all of the design benefits of the standard Cutler-Hammer® switch including the visible double-break, quick-make, quick-break rotary blade mechanism with two contact points per pole.

Standard Features

- NEMA 4X non-metallic enclosure.
- Padlockable enclosure.
- Handle padlockable in the OFF position.
- Six-point door hold-down for superior fluid ingress prevention.
- Six-point mounting with concealed hardware.
- Continuous Polyurethane seal.

- Interlocking mechanism with defaeter.
- Horsepower rated.

Optional Features

- Clear cover.
- EnviroLine stainless steel mechanism.

Standards and Ratings

- UL® 98 Standard for enclosed deadfront switches.
- UL 50 Standard for enclosures for electrical equipment.
- NEMA KS-1.
- 600 Vac maximum.
- 30 – 200 ampere, 3-pole.



Halyester switch can be padlocked in the OFF position by extending handle loop.